

Kabeltyp	Durchmesser (mm)	Biegeradius min (mm)	Z (Ohm)	Verkürzfaktor	Kapazität /m (pf)	Dämpfung (db) pro 100m bei Frequenz im MHz								Max. HF-Betriebsspannung	Bemerkungen	
						10	28	50	100	145	430	1000	1296			
Aircom +	10.8	55	50	0.85	84.00	1.90		2.70	3.30	4.50	8.20		15.20		5000	
Aircell 7	7.3	25	50	0.83	74.00		3.70	4.80	6.60	7.90	14.10		26.10			UV stabilisiertes PVC
CX 5S	6.8	35	75	0.8	55.00			5.10		12.00			24.00			doppelt geschirmt
H 2000	10.3	50	50	0.83	80.00		2.00	2.70	3.90	4.80	8.50	13.80	15.70			
H 43	9.8	100	75	0.85	52.00	1.20		2.50	3.70	4.70	8.00	11.00	14.80			75 R Version H100
H 100	9.8	150	50	0.84	79.00		2.00	2.80	3.70	4.90	8.80		16.00			
H 155	5.4	35	50	0.79	100.00		4.90	6.50	9.40	11.20	19.80		34.90			
H 500	9.8	75	50	0.81	82.00	1.30		2.90	4.10	5.10	9.30		16.80			
3S60	6.0	40	60	0.66	85.00				10.00							
RG 5	8.4	n/a	52.5	0.66	93.50											
RG-5/U	8.4	n/a	50	0.66	29.50	0.66			2.40			8.80				
RG-5B/U	8.4	n/a	50	0.66	96.70				2.10	7.90		28.90			3000	
RG 6	6.8	n/a	75	0.66	20.50	0.80			2.70						2700	
RG-6A/U	8.4	n/a	75	0.66	65.60	2.55			9.50			36.80			2700	
RG-8A/U	10.3	n/a	50	0.66	100.00	1.80			6.60			26.24			4000	
RG-9/U	10.6	n/a	51	0.66	98.40	1.86			6.60			23.90			4000	
RG-9B/U	10.8	n/a	50	0.66	100.00	2.00			6.90			29.60			4000	
RG-10A/U	12.1	n/a	50	0.66	54.00	1.80			6.60			26.20				
RG-11A/U	10.3	50	75	0.66	54.00	2.30			7.50			25.60			4000	75 R Version RG 213
RG-12A/U	12.1	n/a	75	0.66	54.00	2.20			7.50			26.20				
RG-13A/U	10.8	n/a	75	0.66	54.00	2.20			7.50			26.20				
RG-14A/U	13.8	n/a	50	0.66	40.00	1.34			4.60			18.00				
RG-16/U	16.0	n/a	52	0.67	52.48	1.30			3.90			22.00				
RG-17A/U	22.1	n/a	50	0.66	28.00	0.75			2.60			15.60				
RG-18A/U	24.0	n/a	50	0.66	28.00	0.75			2.60			15.60				
RG-19A/U	28.5	n/a	50	0.66	25.30	0.56			2.30			11.50				
RG-20A/U	30.4	n/a	50	0.66	25.30	0.56			2.30			11.50				
RG-21A/U	8.4	n/a	50	0.66	98.40	14.40			42.60			141.00				
RG-29/U	4.7	n/a	53.5	0.66	94.00	3.90			14.40			52.50				
RG-34A/U	16.0	n/a	75	0.66	67.20	0.95			4.30			19.60				
RG-34B/U	16.0	n/a	75	0.66	70.50	1.00			4.60			19.10				
RG-35A/U	24.0	n/a	75	0.66	67.00	0.78			2.80			14.50				
RG-54A/U	6.4	n/a	58	0.66	87.00	2.40			10.10			37.80				
RG-55/U	5.3	n/a	53.5	0.66	93.00	4.30			15.70			55.80				
RG-55A/U	5.5	n/a	50	0.66	97.00	4.30			15.70			55.80				

Kabeltyp	Durchmesser (mm)	Biegeradius min (mm)	Z (Ohm)	Verkürzfaktor	Kapazität /m (pf)	Dämpfung (db) pro 100m bei Frequenz im MHz								Max. HF-Betriebsspannung	Bemerkungen	
						10	28	50	100	145	430	1000	1296			
RG-58/U	5.0	30	53.5	0.66	93.00	4.10			15.20			57.40				
RG-58C/U	5.0	30	50	0.66	98.00	4.60	8.00	11.00	16.10	18.00	34.00	78.80		2500		
RG-59A/U	6.2	30	75	0.66	67.00	3.60			11.20			39.40				
RG-59B/U	6.2	30	75	0.66	69.00	3.60			11.20	14.50	26.00	39.40		4000		
RG-62A/U	6.2	40	93	0.84	43.00	2.80			10.50	13.00	24.00	32.50	(800MHz)	1500	Grieder Typ KXY.62	
RG-74A/U	15.6	n/a	50	0.66	98.40	1.25			4.90			19.70				
RG-83/U	10.3	n/a	35	0.66	144.00	2.60			9.10			31.50				
RG-142 B	5.0	n/a	50	0.69	29.20	1.10			3.90			13.50				Teflon-Isolation
RG-174/C	2.6	15	50	0.66	30.00	3.30			30.00	40.00	72.00			2000		
RG-179	2.6	15	75	0.66												Teflon-Isolation
RG-188	2.6	15	50	0.66										1500		Teflon-Isolation
RG 213 C/U	10.3	110	50	0.66	101.00	2.20	3.10	4.40	7.20	8.50	17.30		27.50	6000		
RG-214	12.0	120	50	0.66												doppelt geschirmt
RG-218/U	22.1	180	50	0.66	97.00	0.66			3.30			14.40				
RG-220A/U	28.5	240	50	0.66	97.00	0.66			3.30			14.40				
RG-223	5.4	25	50	0.66	101.00		7.90	11.00	15.40	17.60						doppelt geschirmt, versilbert
RG-316			50													Teflon-Kabel
UR43	5.0	n/a	52	0.66	95.00	4.26			14.10			59.40		UK-Typ	Komp. Vergleichstyp RG-58-U	
UR57	10.3	n/a	75	0.66	67.00	2.00			6.30			23.30		UK-Typ	Komp. Vergleichstyp RG-11A/U	
UR63	21.7	n/a	75	0.96	46.00	0.50			1.70			5.60		UK-Typ		
UR67	10.3	n/a	50	0.66	98.00	2.00			6.60			24.60		UK-Typ	Komp. Vergleichstyp RG-213/U	
UR74	22.1	n/a	51	0.66	101.00	1.00			3.30			13.80		UK-Typ	Komp. Vergleichstyp RG-218/U	
UR76	5.0	n/a	51	0.66	95.00	5.25			17.30			72.20		UK-Typ	Komp. Vergleichstyp RG-58C/U	
UR77	22.1	n/a	75	0.66	67.00	1.00			3.30			13.80		UK-Typ	Komp. Vergleichstyp RG-164/U	
UR79	21.7	n/a	50	0.96	69.00	0.50			1.70			5.90		UK-Typ		
UR83	14.1	n/a	50	0.96	69.00	0.80			2.60			9.18		UK-Typ		
UR85	14.1	n/a	75	0.66	46.00	0.70			2.30			8.20		UK-Typ		
UR90	6.2	n/a	75	0.66	66.00	3.60			11.40			40.40		UK-Typ	Komp. Vergleichstyp RG-59/B/U	
TV-Kabel (GGA)	5.0	40	75		67.00				13.40			52.80	(1350 MHz)			Grieder Typ KIK.D
TV-Kabel (GGA)	6.6	40	75		55.00				5.20	11.00	25.00		(1750 MHz)			Grieder Typ KIK